ThinkCentre M715 Tiny (2nd Gen) 10VG001D++

Product

ThinkCentre M715a Tiny 2nd Gen

Region

EMEA

Machine Type

10VG

TopSeller

No

Processor

AMD Ryzen 5 2400GE (4C, 3.2 / 3.8GHz, 2MB)

vPro No

Graphics

Integrated AMD Radeon RX Vega 11 Graphics

Monitor Cable

None

Memory

8GBx1

Storage 256GB SSD M.2 PCIe NVMe Opal

Optical

None

WLAN + Bluetooth

RTL8821CE ac, 1x1 + BT4.2

Ethernet

Integrated

Optional Rear Ports

HDMI

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

Adapter Cage

Toolless Chassis Screw

Toolless Chassis Screw

Speaker

1.5Wx1

Dust Filter

None

VESA Mount

VESA Mount

Stand

None

Keyboard / Mouse

USB / USB

Operating System

Windows 10 Pro 64

Warranty

3-year, Onsite

End of Support

Aug 20, 2024

Ann Date (mm/yy)

07/18

Note:

* Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "**" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



WWW.LENOVO.COM

This publication was developed for products and services oered in the United States and E.M.E.A countries. Lenovo may not oer the products, services or features discussed in this document in other countries. Lenovo may withdraw an oering at any time. Information is subject to change without notice. Consult your local representative for information on oerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.



http://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2017. All rights reserved.

ThinkCentre M715 Tiny (2nd Gen) Platform Specifications

Processor	AMD Athlon, A6, A10,	A12, or	Ryzen proces	sor			Security features	 Security slot (in rear for optional Kensington® MicroSaver® cable) Padlock loop Smart USB protection, allows keyboard/ mouse only, blocks all storage devices Power-on password Administrator password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch 		
	Processor	Cores / Threads	Frequency Base/Max	L2 Cache	Memory Support (Up to)	Integrated Graphics				
	Athlon 200GE	2/4	3.2 GHz	1 MB	DDR4-2933	Radeon Vega 3				
	Athlon PRO 200GE	2/4	3.2 GHz	1 MB	DDR4-2933	Radeon Vega 3	 Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black		
	PRO A6-8570E	2/2	3.0 / 3.4 GHz	1 MB	DDR4-2400	Radeon R5	1	Some: Lenovo Calliope Reyboard (USB connector), black Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case		
	PRO A10-8770E	4/4	2.8 / 3.5 GHz	2 MB	DDR4-2400	Radeon R7				
	PRO A6-9500E	2/2	3.0 / 3.4 GHz	1 MB	DDR4-2400	Radeon R5	Mouse			
	PRO A10-9700E PRO A12-9800E	4/4	3.0 / 3.5 GHz 3.1 / 3.8 GHz	2 MB 2 MB	DDR4-2400 DDR4-2400	Radeon R7 Radeon R7				
	Ryzen 3 2200GE	4/4	3.2 / 3.6 GHz	2 MB	DDR4-2400 DDR4-2933	Radeon Vega 8	Mechanical			
	Ryzen 3 PRO 2200GE	4/4	3.2 / 3.6 GHz	2 MB	DDR4-2933	Radeon Vega 8	INCONTANTOUT	Toolless chanssis open (need optional toolless chanssis screw)		
	Ryzen 5 2400GE	4/8	3.2 / 3.8 GHz	2 MB		Radeon RX Vega 11		Optional dust filter M715 Gen2 Tiny only: 7.05" W X 7.20" D X 1.36" H		
	Ryzen 5 PRO 2400GE	4/8	3.2 / 3.8 GHz	-		Radeon RX Vega 11				
Mamari							J -	179mm W X 182.9mm D X 34.5mm H		
Memory	32GB max, DDR4 2666*, two 260-pin SO-DIMM sockets, dual-channel capable * System automatically clocks down for the lower memory controller							2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation		
Disk Optical	Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s * 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s Some: DVD-ROM, 9.0mm high, via USB external ODD box Some: DVD±RW, 9.0mm high, via USB external ODD box						VESA mount Floor Stand			
·							Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models)		
Onboard SATA Graphics	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar						Limited warranty	, ,		
Monitor cable	AMD Radeon™ Graphics in processor, uses main memory, DirectX® 12, two DisplayPort™, one optional port (HDMI, VGA, or 3rd DP), supports 3 independent displays (supports maximum of 2 concurrent HDMI/DVI displays when using HDMI port or DP to DVI/HDMI dongles, and Athlon / Athlon PRO only support 2 displays); Max resolution: 4096x2160 (DP) @ 60Hz; 4096x2160 (HDMI) @ 30Hz; 1920x1200 (VGA) @ 60Hz						Preload	Preloaded operating system Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit Some: Windows 7 Professional 64 preinstalled through downgrade Preloaded applications (only some listed) - WIndows 10 only Lenovo Vantage Microsoft Office preloaded;		
Chipset	Optional DP to VGA dongle, DP to DVI-D dongle, or DP to HDMI 1.4 dongle					1.4 dongle		rights in Windows 10 Pro 64-bit	purchase a product key to activate Cyberlink PowerDVD (only for models	
	AMD B300 Chipset Two USB 3.1 Gen1 (one is Always On and fast charge), one microphone (stereo,								with DVD / DVD±RW) • Cyberlink Power2GO (only for models	
. , ,	3.5mm), one headphone / microphone combo jack (stereo, 3.5mm) One USB 3.1 Gen1 and three USB 2.0, ethernet (RJ-45), two DisplayPort, one headphoneone					ım)			with DVD±RW) ▶ LinkedIn	
Rear ports (Opt.)	One optional port (VGA*, 3rd DP*, HDMI*, or serial on some models) * Not support VGA, 3rd DP, HDMI for the models with Athlon / Athlon PRO High Definition (HD) Audio, Realtek ALC233-VB2 / internal speaker (1.5 watt)							 Windows 7 only Lenovo Solution Center ThinkVantage System Update Create Recovery Media 		
Audio support]			
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 1x1								 Microsoft Office preloaded; purchase a product key to activate Adobe® Reader® 	
	Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377 (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band),					,	Environment	ENERGY STAR® 7.0*, EPEAT™ Gold rating* (*Not for non-OS models); ErP Lot 3; ; RoHS-compliant		
	Wi-Fi + Bluetooth 4.2* combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 2x2						MIL-SPEC test	MIL-STD-810G military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock)		
Bluetooth Ethernet							Accessories	For compatible accessories, please go to http://smartfind.lenovo.com		
Manageability Security chip	DASH 1.0/1.1 Discrete TPM 2.0, TCG Certified									











